

Ganz Genstar NVR-Series



4/8-Channel



16-Channel

With up to 6MP recording are a number of different Ganz IP network recorder available. Starting with the 4-channel up to 16 channel recorder, suitable for numerous applications. Ideally matched to the recorder, incidentally, are the IP cameras from Ganz Genstar series.

- Up to 6 Megapixel recording
- Either 4, 8 or 16 channels
- Up to 25 frames / second
- H.264-Compression
- App for iOS & Android

Order data

Order number	Product description
NR8-4M71	H.264 4-Channel NVR, max. 6MP recording, 4x RJ-45 (PoE), HDMI / VGA, 1x SATA-interface, 2x USB, RJ-45, 255 x 47.5 x 235, 930g
NR8-8M71	H.264 8-Channel NVR, max. 6MP recording, 8x RJ-45 (PoE), HDMI / VGA, 1x SATA-interface, 2x USB, RJ-45, 372 x 44.5 x 311, 2.8kg
NR8-16M74	H.264 16-Channel NVR, max. 6MP recording, 16x RJ-45 (PoE), HDMI / VGA, 4x SATA-interface, 3x USB, RJ-45, 440 x 67 x 376, 3.6kg
NR8-16M74-0	H.264 16-Channel NVR, max. 6MP recording, 2x RJ-45, HDMI / VGA, 4x SATA-interface, 3x USB, RJ-45, 440 x 67 x 376, 3.6kg

Ganz Genstar NVR-Series



	NR8-4M71	NR8-8M71	NR8-16M74	NR8-16M74-0
Resolution	6MP/5MP/4MP/3MP/1080P/720P/D1			
Compression	H.264			
Video Input	4 x RJ-45 (PoE)	8 x RJ-45 (PoE)	16 x RJ-45 (PoE)	2 x RJ-45 (w/o PoE)
Channel	4	8	16	
Monitor Output	1x HDMI / VGA (simultaneously)			
Audio Input	-	1		
Audio Output	-	1		
Alarm Input	-	-	2	1
Alarm Output	-	-	2	1
Hard Disk Quantity	1 (optional) max. 4TB per HDD		4 (optional) max. 4TB per HDD	
Operating System	LINUX			
Recording Format	6MP/5MP/4MP/3MP/1080P/720P/D1			
Recording Mode	Continuous / Motion / Alarm			
Recording Speed	6MP/5MP/4MP/3MP@15fps; 1080P@25fps			
Recording Rate	4 Channel Max 80Mbps	8 Channel Max 80Mbps	16 Channel Max 128Mbps	
Events	Motion/ Video loss/ External Alarm			
Motion Detection	Controlled by camera			
Interfaces	2x USB, RJ-45		3x USB, 2x RJ-45	
Time/date Settings	GMT Timezone, Auto DST, NTP			
Remote Access	Firefox, Chrome, Safari, IE, iPhone, iPad, Android			
Data Export	USB, HDD			
Protocols	RTP/RTCP, TCP/UDP, HTTP, DHCP, DNS, NTP			
Access Authorisation	Password protection			
Operating Temperature	0° - 45°C		-10° - 45°C	
Operating Voltage	48VDC		110/220VAC	
Dimensions (WxHxD) mm	255 x 47.5 x 235	372 x 44.5 x 311	440 x 67 x 376	440 x 89.9 x 435
Weight	930g	2.8kg	4.0kg	7.2kg